



FEATURES

- H.264 Main Profile level
- 2 Megapixel Full HD 1920x1080P Resolution
- Dual H.264 Stream, resolution, frame rate, bit rate adjustable
- Onvif Compliant
- Support plug in & play,
- Support Day/Night
- indoor Use for hidden camera
- ideal for ATM machine

TECHNICAL SPECIFICATIONS

Model		MT-IPPH36
Video Processor	ONVIF protocols	Support
	Compression Technology	Dual Steam H.264
	Frame Rate	Real time 30fps
	Video Protocol	1 x RJ45, 10/100M, support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
	Function	Support WEB configuration, OSD, realtime video transmitting, support motion detect and IO alarm activated to remotely recording,screen pop up, message,playback and download, support JPEG capture, support CMS&MYEYE, SDK available
	Motion	ON/ OFF (Sensitivity adjustable)
	Bit Rate	32Kbps ~ 12Mbps
	Video	H.264 compression,support dual stream, A/V format, stream:0.1M~6Mbps; frame:1~30fps
	Resolution	Main stream:1920*1080;Sub stream:704*576

Camera Parameter	Sensor Type	1/2.7" SONY IMX222 super low illumination CMOS sensor
	Effective pixel	Effective pixel 2.0 MegaPixels
	Lens	3.6mm
	Minimum illumination	color 0.01Lux/F1.2, B/W 0.001 Lux/F1.2
	Shutter time	1/25 ~ 1/1000 sec
	Image optimization	Flaw picture adjusts/ Image vibration adjusts/ Reversed light compensation adjusts
	Eliminate flicker	Auto/ Off/ Manual (50Hz/60Hz)
	White Balance	Auto/ Manual
Working environment	Function	Support WEB configuration, realtime video transmitting, support motion detect and IO alarm activated to remotely recording,screen pop up,message, playback and download, support JPEG capture, support CMS&MYEYE, SDK available,Mirror
	Mobile Monitor	Support iPhone,Windows Mobile,BlackBerry,Symbian,Android
	Fan / Heater	Auto
	Covering	IP55
	LAN port	10/100M Base-T
	Temperature	-20° ~ 50°
	Humidity	0% ~ 95% RH
	Connector	RJ45 DC 12V
	Diameter	40x40mm
	Material	All the metal vandal resistant
	Weight	0.35kg