



FEATURES

- 24 porte 10/100Mbps PoE Ethernet a lunga distanza, 2 porte Uplink Ethernet 1000Mbps e 2 porte 1000Mbps ottiche
- Management Layer 2
- Standard IEEE802.3 af/at
- Tecnologia advanced network cable driver, distanza di trasmissione fino a 150m o 200m programmabili
- Nessun rischio di danneggiare dispositivi non POE
- Porte PoE Ethernet IEEE802.3 AF forniscono 30W, ideali anche per telecamere con infrarossi ad alto consumo, totale di 380W
- Rispetta gli standard IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3ab 1000BASE-T, IEEE802.3z 1000BASE-SX/LX
- Montaggio a rack su frontale o retro

TECHNICAL SPECIFICATIONS

| Model | MT-TP7224E-POE | |
|-------------------|--|--|
| Power | Power Supply | Mains on load |
| | Power Adapter Voltage | AC 100~240V |
| | Consumption | 430W(Full load) |
| Network Connector | Ethernet Port | 1~24 Ports: 10/100Mbps Ethernet port, adaptive control UPLINK Ethernet port: 10/100/1000Mbps Ethernet port SFP: SFP optical fiber module, 1000Mbps |
| | Transmission Distance | 1~24 ports: Recommended 120m Max. 150m; Uplink 1000Mbps Ethernet port: Max. 100m SFP: depend on the optical module performance |
| | PoE Protocol | IEEE802.3af, IEEE802.3at |
| | PoE Power Supply | End-span |
| | PoE Power Consumption | Each Ports≤30W, Total≤380W |
| Network Switch | Ethernet Standard | IEEE802.3 10BASE-T, IEEE802.3u 100BASE-TX, IEEE802.3ab 1000BASE-T, IEEE802.3z 1000BASE-SX/LX |
| | Switch Capacity | 16G |
| Management | Management | Management L2 |
| Protection | ESD | Level 3, Per: IEC61000-4-2 |
| | Communication Port Lighting Protection | Level 3, Per: IEC61000-4-5 |
| Environmental | Working temperature | 0°C~55°C |
| | Storage temperature | -40°C~85°C |
| | Humidity (non-condensing) | 0~95% |
| Mechanical | Dimension (L×W×H) | 442mm×315mm×44mm |
| | Material | Sheet metal |
| | Color | Black |
| | Weight | 3.73kg |

Datasheet rev.A15.5

Application

