



FEATURES

- HD CMOS camera
- Aluminum panel, IP65,IK08
- ICR Night vision &Voice indication
- Video & Audio messaging
- Remote intercom with mobile APP
- Surface mounted

TECHNICAL SPECIFICATIONS

Model		MT-V3211E
System	Main Processor	Embedded Micro Processor
	Operation System	Embedded LINUX OS
Video	Video Compression	H.264
	Image Sensor	1/2.8" 2MP CMOS
	Focal Length	1.9mm
	Angle of View	H:140°
	Day/Night	ICR
Audio	Audio Compression	G.711
	Audio Input	Omnidirectional Mic
	Audio Output	Built-in Speaker
	Bidirectional Talk	Support Dual-way Bidirectional talk
Operation Mode	Keypad	2 Mechanical Buttons
	Reader	Mifare Card
Interface	Door Control	1
	Alarm In	2(1ch unlock button, 1ch feedback)
	RS485	1
Network	Ethernet	10M/100Mbps Self-adaptive
	Network Protocol	TCP/IP
	Ethernet	10M/100Mbps Self-adaptive
	Network Protocol	TCP/IP
General	Ingress Protection	IP65, IK08
	Tamper Switch	1
	Installation	Surface
	Material	Aluminum
	Power	DC 12V, PoE(802.3af)
	Power Consumption	Standby ≤1W, Work ≤7W
	Working Temperature	-40°C~+60°C
	Relative Humidity	10%~90%RH
	Dimensions	182.0mm×30.0mm×101.0mm
	Weight	0.8Kg