



## FEATURES

- HD CMOS camera
- Zinc alloy panel, IP65,IK10
- ICR Night vision &Voice indication
- Video & Audio messaging
- TCP/IP,SIP
- Surface mounted

## TECHNICAL SPECIFICATIONS

Model		MT-V2101
System	Main Processor	Embedded Micro Processor
	Operation System	Embedded LINUX OS
Camera	Image Sensor	1/2.7" 2MP CMOS
	Focal Length	2.8mm
	Angle of View	H:100°
	Angle of View adjustment	Horizontal: -45° ~ +45°
Video	Video Compression	H.264
	Video Streaming	Dual Stream
	Day/Night	Auto(ICR), 5m
	BLC Mode	WDR
	White Balance	Auto/Natural/Street Lamp/Outdoor/Manual
	Gain Control	Auto/Manual
	White Balance	Support
Audio	Audio Compression	G.711
	Audio Input	Omnidirectional Mic
	Audio Output	Built-in Speaker
	Bidirectional Talk	Support Dual-way Bidirectional talk
	Audio processing	Noise suppression, Echo cancellation
Operation Mode	Keypad	2 Mechanical Buttons
Interface	Door Control	1
	Alarm In	1
	RS485	1
Network	Ethernet	10M/100Mbps Self-adaptive
	Network Protocol	TCP/IP, SIP
General	Ingress Protection	IP65, IK10
	Tamper Switch	1
	Tamper Screw	Support
	Installation	Surface
	Material	Front Panel: Zinc alloy Rear Panel: Aluminum alloy Holder: Aluminum alloy
	Power	DC 12V, PoE(802.3af)
	Power Consumption	Standby ≤2.5W, Work ≤7W
	Working Temperature	-40°C~+60°C
	Relative Humidity	10%~90%RH
	Dimensions	163.0mm×73.0mm×54.5.0mm
Weight	0.8Kg	