

MT-IPSCX700IP

Telecamera IP Full HD underwater rugged camera per applicazioni subacquee e ambienti marini



FEATURES

- Custodia in acciaio INOX316L
- Immersione fino a 50 metri 500-Kpa
- Full HD 1080P
- ONVIF
- Illuminatore integrato

TECHNICAL SPECIFICATIONS

Model		MT-IPSCX700IP	
Camera	Image Sensor	1/2.8" 2Megapixel progressive scan CMOS	
	Effective Pixels	1920(H) * 1080(V)	
	Scanning System	Progressive	
	Electronic Shutter Speed	Auto/Manual, 1s~1/30000s	
	Min. Illumination	Color 0.001Lux F1.2, BN 0.0001Lux F1.2	
	S/N Ratio	More than 50dB	
Camera Features	Day/Night	Auto(ICR)/Color/B/W	
	Backlight Compensation	BLC / HLC / WDR	
	White Balance	Auto/Manual	
	Gain Control	Auto/Manual	
	Noise Reduction	3D	
	Smart light	Light sensor 3 white led or 4 IR led	
Lens	Focal Length	2mm	
	Max Aperture	F2.1(F2.0)	
	Angle of View	95°	
Video	Compression	H.265/ H.264	
	Resolution	1080P(1920x1080)/720P(1280x720)/ D1(704x576/704x480) / CIF(352x288/352x240)	
	Frame Rate	Main Stream	1080P(1 ~ 25fps)
		Sub Stream	D1(1 ~ 25/30fps)
Bit Rate	H.264: 4kbps~8192bps		
Network	Ethernet	RJ-45 (10/100Base-T)	
	Protocol	IPv4/IPv6, HTTP, HTTPS, TCP/IP, UDP, UPnP, ICMP, IGMP, RTSP, RTP, SMTP, NTP, DHCP, SDK Secondary development	
	Compatibility	ONVIF, NVR hikvision, dahua	
	Max. User Access	20 users	
	Smart Phone	iPhone, iPad, Android,	
	General	Power Supply	DC12V 6W - PoE (802.3af) optional
Size		70 x 140mm	
Working Environment		-20°C~+55°C	
Protection		IP68	
Housing		INOX316L	

Datasheet rev.A18m



The default length is 5 meters (the longest is no more than 100 meters), PU material, Diameter 6.3MM. Resistance to 60KG pull, Anti-aging, Anti-friction, Resistance to seawater corrosion, Special underwater