



### FEATURES

- 1/2.7" 4Megapixel progressive scan CMOS
- Day/Night(Electronic), WDR
- 2.8mm Fixed Pinhole Lens
- 8-meters cable
- Require a Main Box to work together

### TECHNICAL SPECIFICATIONS

Model	MT-IPHUM84SP			
Camera	Image Sensor	1/2.7" 4Megapixel progressive scan CMOS		
	Scanning System	Progressive		
	Effective Pixels	2688(H)x1520(V)		
	Minimum Illumination	0.02Lux/F2.4 (Color,1/3s,30IRE) 0.08Lux/F2.4 (Color,1/30s,30IRE) 0.01Lux/F2.4 (B/W,1/3s,30IRE) 0.04Lux/F2.4 (B/W,1/30s,30IRE)		
Lens	Lens Type	Fixed		
	Mount Type	Board-in		
	Focal Length	2.8mm		
	Max. Aperture	F2.4		
	Angle of View	H:83.4° ,V:44.9°		
	Focus Control	Fixed		
	DORI Distance	Detect	61m(200ft)	
		Observe	24m(80ft)	
Recognize		12m(40ft)		
Identify		6m(20ft)		
Certifications	CE (EN 60950:2000) UL:UL60950-1 FCC: FCC Part 15 Subpart B			
Audio	Operating Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH		
	Storage Conditions	-30° C ~ +60° C (-22° F ~ +140° F) / Less than 95% RH		
Construction	Casing	Metal		
	Dimensions	Φ30.5mm×48.65mm (Φ1.20"×1.91")		
	Net Weight	0.40Kg (0.88lb)		
	Gross Weight	0.47Kg (1.03lb)		

Datasheet rev.A18.8

