



FEATURES

- 1-port HDMI input with built-in audio extraction
- H.264 video encoding, up to 1920x1080 Full HD resolution
- Multiple streaming protocols: RTMP, RTSP, HTTP FLV, HLS, UDP/RTB multicast
- Flexible coding resolution from 176x144 up to 1920x1080, same as input resolution
- CBR/VBR stream control with adjustable bit rate 32-32000 kbit
- Multi-format audio coding: AAC+, AAC++, MP3, MP2, AC3
- OSD overlay with text, picture and scrolling text support, up to 4 areas
- Gigabit Ethernet network interface, ONVIF compatible
- Compact design 10.4 x 10.4 x 2.7 cm, wall-mountable
- Low power consumption 4W, DC 12V supply

MT-HDE8800AH-2

TECHNICAL SPECIFICATIONS

| Network | |
|--------------------------|--------------------------------------|
| Network | Gigabit Ethernet |
| Configuration Management | Configuration management via the WEB |
| ONVIF | Support ONVIF search browsing videos |

| Structure | |
|------------|---|
| Dimensions | 104 mm x 104 mm x 27 mm (includes wall hanging) |

| Audio and Video Input | |
|-----------------------|----------------------------|
| Video Input | 1 port HDMI |
| Audio Input | 1 port HDMI built-in audio |

| Audio Coding | |
|----------------------------|--|
| Coded Sampling Rate | 44100 / 48000 optional |
| Coding Method | AAC+ / AAC++ / MP3 / MP2 / AC3 optional |
| Coding Bit Rate | AAC: 48000-320000 adjustable / AAC+: 2400-48000 adjustable / AAC++: 12000-320000 adjustable / MP3: 64000-320000 adjustable / MP2: 64000-320000 adjustable / AC3: 40000-640000 adjustable |
| Digital Volume | -50 to 50 adjustable |
| RTSP Stream G711A Encoding | Disable / Enable optional |

| OSD | |
|------------------|---------------------------------------|
| Transparency | 0-128 adjustable |
| Type | Text / Picture / Scrolling text |
| Area | 4 areas available |
| X Coordinate | 0-1920 |
| Y Coordinate | 0-1080 |
| LOGO | 4 logos can be uploaded for selection |
| Font Size | 8-72 |
| Background Color | Transparent / White / Black |
| Font Color | RGB color is optional |

| Power | |
|-------------------|------------|
| Power Supply | DC 12V, 1A |
| Power Consumption | 4W |

| Environment | |
|-----------------------|---------------------------------|
| Operating Temperature | -20°C to +60°C (-4°F to +140°F) |
| Operating Humidity | <90% no condensation |

| Video Coding | |
|---------------------|--|
| Coding Type | H.264 |
| Coded Frame Rate | 5-60 adjustable |
| Key Frame Interval | 5-300 adjustable |
| Bit Rate (kbit) | 32-32000 adjustable |
| Coding Resolution | 1920x1080 / 1680x1056 / 1280x720 / 1024x576 / 850x480 / 720x576 / 720x540 / 720x480 / 720x404 / 704x576 / 640x480 / 640x360 / 608x448 / 544x480 / 480x480 / 480x384 / 480x360 / 480x332 / 480x272 / 480x270 / 400x320 / 400x224 / 352x480 / 352x228 / 320x256 / 320x240 / 320x180 / 240x180 / 176x144 / Same as input resolution |
| Code Stream Control | CBR / VBR optional |
| Stream | RTMP / RTSP / HTTP FLV / HLS / UDP multicast / RTB multicast |