




FEATURES

- 1/2.8" 2 Megapixel CMOS
- 25/30fps@1080P
- High speed, long distance real-time transmission
- HD or SD BNC output
- OSD Menu, control over coaxial cable
- True WDR, Day/Night(ICR), AWB, AGC, BLC, DNR
- AHD, HD-CVI, HD-TVI, PAL
- DC12V

TECHNICAL SPECIFICATIONS

Model	MT-HDCS3200H	
Camera	Image Sensor	1/2.8" Sony Sony CMOS - STARVIS
	Effective Pixels	1920(H) x 1080V
	Electronic Shutter	1.3s~1/30,000s
	Video Frame Rate	25/50fps@720P; 25fps@1080P
	Synchronization	Internal
	Mini. Illumination	0.01Lux/F1.4 (color); 0.001Lux/F1.4 (B/W)
	Video Output	AHD, HD-CVI, HD-TVI, PAL
Camera Features	Day/Night	Auto(ICR) / Color / B/W
	Noise Reduction	2D/3D
	OSD Menu	Support
Lens	Lens Type	Manual
	Mount Type	C/CS
Auxiliary Interface	RS485	-
	Alarm	-
	Audio	-
General	Power Supply	DC12V±25%
	Power Consumption	Max 4.7W
	Working Environment	-30°C~+60°C / Less than 95%RH (no condensation)
	Transmission Distance	Over 500m via 75-3 coaxial cable
	Dimensions(W×D×H)	38mm×48mm×38mm
	Weight	0.3kg
	Material	Metal