



FEATURES

- Made from aluminum alloy and SUS 304 stainless steel
- Suitable for a variety of cameras, elegant design
- Designed for multiple types of poles (80 mm–150 mm diameter)
- Load bearing capacity: 3.0 kg (6.61 lb)
- Wide operating temperature range: -40 °C to +60 °C
- Easy and fast installation

TECHNICAL SPECIFICATIONS

Structure	
Casing Material	Aluminum alloy; Hoop: SUS304
Product Dimensions	125.6 mm x 114.0 mm x 20.0 mm (4.94" x 4.49" x 0.79") (L x W x H)
Appearance Color	White
Net Weight	0.26 kg (0.57 lb)
Gross Weight	0.36 kg (0.79 lb)
Load Bearing	3.0 kg (6.61 lb)
Installation	Pole mount
Pole Diameter	80 mm - 150 mm (3.15" - 5.91")
Packaging Dimensions	146.0 mm x 65.0 mm x 147.0 mm (5.75" x 2.56" x 5.79") (L x W x H)

Environment	
Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Operating Humidity	< 90% (RH)
Storage Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
Storage Humidity	10% - 90% (RH)
Anti-corrosion Level	Basic Protection

MT-MFA152E

DIMENSIONS

