



FEATURES

- Keyboard to Control
 - Mtechnology High Speed Dome
 - Mtechnology Standalone DVR
 - Mtechnology Network High Speed Dome
 - Network Video Server
- Connection RS485, RS422, USB, RS232 & Network
- Three Dimensional Joystick Control of PTZ Functions
- Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control
- Auxiliary Functions
- On-Screen Menu & User Operation Procedure Tips
- Connect to MTechnology Suite via USB

TECHNICAL SPECIFICATIONS

Model		MT-KBDIPB
General	Keyboard Keypanel	Electromechanical
	Joystick	3-axis, vector-solving, with twisting, return to-center head
	Keyboard Connector	RJ-45, RS232, RS485, RS422, USB
	Keyboard Communication	Direct Mode, Network Mode
	Direct Mode	Interface: RS232/RS485 DVR Protocol: DH2 Dome Protocol: MT-SD/PELCO-D/PELCO-P/PELCO-D1/PELCO-P1..
	Network Mode	Interface: RJ45 DVR/Network Dome: IP Address/Port/Protocol
	Display	LCD, 75.2mm x 33.85mm
Environmental	Power Supply	Power adapter, input 100V~240V 50Hz / 60Hz, output DC12V/1000mA
	Power Consumption	5W
	Working Temperature	-10°C~+55°C
	Working Humidity	10%~90%
	Atmosphere Pressure	86kpa~106kpa
	Dimension	330mmx160(140)mmx37.5(21)mm (W× D×H) (height: 100mm including joystick)
	Weight	2.5KG